

## **GP Series**




### **Radon Mitigation Fan**

All RadonAway™ fans are specifically designed for radon mitigation. GP Series Fans offer a wide range of performance options that make them ideal for most sub-slab radon mitigation systems.

### **Features**


- Quiet operation
- Water-hardened motor
- Seams sealed under negative pressure (to inhibit radon leakage)
- Mounts on duct pipe or with integral flange
- 3" diameter ducts for use with 3" or 4" pipe
- Electrical box for hard wire or plug in
- ETL Listed for indoor or outdoor use
- 4 interchangeable GP models

| MODEL | P/N     | FAN DUCT<br>DIAMETER | WATTS  | MAX.<br>PRESSURE"WC | TYPICAL CFM vs. STATIC PRESSURE WC |      |      |      |      |      |      |
|-------|---------|----------------------|--------|---------------------|------------------------------------|------|------|------|------|------|------|
|       |         |                      |        |                     | 1.0"                               | 1.5" | 2.0" | 2.5" | 3.0" | 3.5" | 4.0' |
| GP201 | 23007-1 | 3"                   | 40-60  | 2.0                 | 82                                 | 58   | 5    | -    | -    | -    | -    |
| GP301 | 23006-1 | 3"                   | 55-90  | 2.6                 | 92                                 | 77   | 45   | 10   | -    | -    | -    |
| GP401 | 23009-1 | 3"                   | 60-110 | 3.4                 | 93                                 | 82   | 60   | 40   | 15   | -    | -    |
| GP501 | 23005-1 | 3"                   | 70-140 | 4.2                 | 95                                 | 87   | 80   | 70   | 57   | 30   | 10   |





All RadonAway inline radon fans are covered by our 5-year, hassle-free warranty





# RP Series



## Radon Mitigation Fan


All RadonAway™ fans are specifically designed for radon mitigation. RP Series Fans provide superb performance, run ultra-quiet and are attractive. They are ideal for most sub-slab radon mitigation systems.

#### **Features**


- Energy efficient
- Ultra-quiet operation
- Meets all electrical code requirements
- Water-hardened motorized impeller
- Seams sealed to inhibit radon leakage (RP140 & RP145 double snap sealed)
- RP140 and RP260 Energy Star® Rated
- ETL Listed for indoor or outdoor use
- Thermally protected motor
- Rated for commercial and residential use


| MODEL  | P/N     | FAN DUCT<br>DIAMETER | WATTS  | MAX.<br>PRESSURE"WC | TYPICAL CFM vs. STATIC PRESSURE WC |     |      |      |      |  |
|--------|---------|----------------------|--------|---------------------|------------------------------------|-----|------|------|------|--|
| MODEL  |         |                      |        |                     | 0"                                 | .5" | 1.0" | 1.5" | 2.0" |  |
| RP140* | 23029-1 | 4"                   | 15-21  | 0.8                 | 135                                | 70  | -    | -    | -    |  |
| RP145  | 23030-1 | 4"                   | 41-72  | 2.1                 | 166                                | 126 | 82   | 41   | 3    |  |
| RP260* | 23032-1 | 6"                   | 50-75  | 1.6                 | 272                                | 176 | 89   | 13   | -    |  |
| RP265  | 23033-1 | 6"                   | 91-129 | 2.3                 | 334                                | 247 | 176  | 116  | 52   |  |
| RP380* | 28208   | 8"                   | 95-152 | 2.3                 | 497                                | 353 | 220  | 130  | 38   |  |











| Model | Α    | В      | С      |  |
|-------|------|--------|--------|--|
| RP140 | 4.5" | 9.7"   | 8.5"   |  |
| RP145 | 4.5" | 9.7"   | 8.5"   |  |
| RP260 | 6"   | 11.75" | 8.6"   |  |
| RP265 | 6"   | 11.75" | 8.6"   |  |
| RP380 | 8"   | 13.41" | 10.53" |  |

For Further Information Contact